

GT 204 Digital Video Recorder



Features:

- ❑ Triplex function: live/record/network
- ❑ 4 video inputs with loop-through
- ❑ Record maximum 100fps (real time record/playback)
- ❑ Provides channel masking
- ❑ Remote Viewing via TCP/IP: live/play/backup
- ❑ Supports multi languages: English, traditional Chinese, Japanese, French)
- ❑ Alarm: input x 4 / output x 1 (NC, NO)
- ❑ Audio: input x 1 / output x 1
- ❑ Alarm/motion/Vloss/HDD full/HDD crash
- ❑ Data backup: USB interface / network / CDRW
- ❑ Hard disk data readable in PC (Video Viewer Application)
- ❑ IR remote controller

Specification:

Channel input	4 x inputs: 1.0Vp-p, 75ohm unbalanced (BNC type)
Output	4 x video looping out (BNC), 1 x monitor out, 1 x S-Video
Horizontal resolution	720x480 (NTSC) / 720x576 (PAL)
S/N ratio	>40dB
Colour	16.7 Million
Monitoring method	
Split screen	1, 4, 9 (live/playback)
Zoom	live/playback 2x2 zoom
Sequence	720(H) x 576(V) active pixels (PAL)
Screen quality	¼ screen: 360(H) x 288(V) active pixels (PAL)
Display rate	120 frames per second (4 x 30)
Recording/Play function	
Recording	1/30, 1/15, 1/10, 1/5, 1/3, 1/2, 1, 2, 3.13, 5, 8.33, 12.5, 25, 50, 100,
Record quality	Super, high, fine, normal, low
Compression	M-JPEG
Record mode	Normal, schedule, motion detect, alarm
Playback mode	Date/time search or event search
Other functions	
Multitasking	Triplex
Motion detect	Motion detect recording and relay on at the same time
Network Function	RJ45, Remote Viewer Driver,
Alarm	Max 4 x alarm / 1 relay output
Back-up	USB / network / CD-RW
RS485	For keyboard control
Storage	Internal 1 or 2 HDD (3.5 IDE interface)
Audio input	RCA x 1
Audio input	RCA x 1
IR remote controller	Standard
Shuttle control input	x 1
Power supply	DC 12V / 5Amp
Weight	NW: 5.8kg GW: 9.1kg
Dimensions	430(W) x 444(D) x 100(H)
Operating temperature	5 °C ~ 40 °C
Operating Humidity	Less than 90%